







# GENERAL SPECIFICATIONS

## Grapple Features

<b>MODEL</b>	<b>1.3 m<sup>2</sup></b>
<b>RECOMMENDED WORKING PRESSURE</b>	<b>230 BAR</b>
<b>RECOMMENDED OIL FLOW</b> Grapple Function	<b>200L/min</b>
Rotator Function	<b>35L/min</b>
<b>WEIGHT</b>	<b>1400 kg</b>
<b>GRIPPING AREA PRACTICAL</b> 	<b>1.3 m<sup>2</sup></b>
<b>MAX GRIPPING WIDTH</b> 	<b>2450 mm</b>
<b>MIN GRIPPING DIAMETER</b> 	<b>220 mm</b>
<b>MAX WIDTH</b> 	<b>830 mm</b>
<b>HEIGHT</b> with max gripping width  with tip to tip 	<b>2000 mm</b>  <b>2100 mm</b>

- Pins are induction hardened
- All pivot points bushed
- Heavy duty cylinder 5.5 inch bore
- Stronger body construction
- All replaceable structure
- All pivot points fitted with greasers
- High clamping force
- Fast action
- Alloy steel construction
- Incorporating an IR22X Indexator rotator
- See Indexator rotator brochure for rotator technical data



**Randalls Equipment Co. (Vic.) Pty. Ltd.**

8 Wallace Avenue, Laverton, Melbourne, Victoria, Australia

Ph: 03 9369 8988

Fax: 03 3969 8683

Email: randalls@randalls.com.au

www.randalls.com.au

DEALER:



# LOG GRAPPLE MODEL 1.3



## RANDALLS 1.3 M2 PULPWOOD GRAPPLE



WIDE OPENING



POSITIVE GRIP SINGLE LOG 20 CM

Low profile design provides greater loading height, alloy steel construction allows low weight combined with high strength.

Ideally suited to 25 tonne plus class carrier.

Our grapples are heavy duty models to cater for all replacements on knuckleboom loaders and as new equipment to excavators.

Rotators and boom links are also available